

CGC

IC-CUSHION LPG
8,000 / 10,000 / 12,000 lbs.
(4000 / 5000 / 5500 kg)



STANDARD SPECIFICATIONS

40/50/55

Manufacturer's Designation		CGC 40	CGC 50	CGC 55
Load Capacity / Rated Load	lbs(kg)	8,000 (4000)	10,000 (5000)	12,000 (5500)
Height Overhead Guard	in(mm)	87.2 (2215)	87.2 (2215)	87.2 (2215)
Width	in(mm)	50.8 (1290)	54.8 (1392)	54.8 (1392)
Right Angle Stack (add load length and clearance)	in(mm)	106.7 (2710)	116.0 (2946)	118.3 (3005)
Outside Turning Radius	in(mm)	89.4 (2270)	98.2 (2494)	99.9 (2537)
Travel speed loaded / unloaded	mph (kph)	12.2 (19.6) / 12.5 (20.1)	12.1 (19.5) / 12.4 (20.0)	11.7 (18.8) / 12.2 (19.6)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	GM / Vortec 4300LT / 93(69) @ 2400	GM / Vortec 4300LT / 93(69) @ 2400	GM / Vortec 4300LT / 93(69) @ 2400

STANDARD FEATURES

Single and two-speed transmissions available • Standard, full free lift triple & quad uprights • Full range of lift heights and options available • High visibility uprights • Isolated operator cell • Full access clamshell hood • GM 4.3 liter V6 LPG • CLARK monitor engine shutdown protection • Two-pedal inch-brake system • Clark safety seat



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.